




China Sanew Cable Co., Ltd.

UL10362 High Temperature PFA Insulated Wire

Product Features: UL10362 High Temperature PFA Insulated Wire is resistant to acids, alkalies, oils, flame retardant, fire, and low smoke, no halogen. And the conductor is solid or stranded silver-plated copper or tinned copper conductor, 10 ~ 36 AWG. The insulation is color-coded PFA which has standard thickness, and is easy stripping and cutting.	The applications: UL10362 High Temperature PFA Insulated Wire is widely applied in aviation; metallurgy and petroleum industry as well as applied in other products such as: electronic instrument & device, electrical appliance, leads for transformer & electrical motor.
--	--

Silver-plated copper or



TECHNICAL DATA:

Conductor:	Silver-plated Copper or Tinned copper
Insulation:	PFA
Temperature Rating:	-80°C to +250°C
Operating Voltage:	600V
Conductor stranding:	Please see the next page
Color Code	According to clients
Approvals:	According to VDE, U

Add: 2-1-101, Binhefang, Daxing District, Beijing, China Zip: 102600 Tel: +86 - 10 - 51265801
E-mail: international@sanew-cable.com Fax: +86 - 10 - 51286576 Website:



China Sanew Cable Co., Ltd.

UL10362 High Temperature PFA Insulated Wire

Size AWG	Conductor		Insulation (mm)		Maximum Resistance at 20°C Ω/km
	Sm stranding No./m	Dia. (mm)	Nominal Thick	Nominal Dia.	
36	1/0.14	0.14	0.20	0.50±0.05	997
34	1/0.16	0.16	0.20	0.52±0.08	758
32	1/0.20	0.20	0.20	0.55±0.08	586
	7/0.08				
30	1/0.25	0.25	0.20	0.60±0.08	408
	7/0.10	0.30		0.65±0.08	
28	1/0.32	0.32	0.25	0.82±0.08	226
	7/0.12	0.35		0.85±0.08	213
26	1/0.40	0.40	0.35	0.90±0.08	145
	7/0.15	0.45		0.95±0.08	138
24	1/0.50	0.50	0.35	1.20±0.08	90.4
	7/0.20	0.60		1.30±0.08	
22	7/0.254	0.76	0.35	1.45±0.11	50.8
	19/0.16	0.80			
20	19/0.19	0.95	0.35	1.65±0.11	33.6
18	19/0.24	1.20	0.35	1.85±0.11	24.6
16	19/0.30	1.50	0.40	2.30±0.16	16.6
14	19/0.37	1.85	0.40	2.65±0.16	9.5
12	19/0.49	2.60	0.45	3.50±0.20	5.7
10	37/0.45	3.15	0.50	4.15±0.20	3.64

Add: 2-1-101, Binhefang, Daxing District, Beijing, China Zip: 102600 Tel: +86 - 10 - 51265801
E-mail: international@sanew-cable.com Fax: +86 - 10 - 51286576